



DETACHABLE DISPLAY.
MORE DATA UPFRONT.
BALANCES TO .02 MICRON.

TAKE IT FOR A SPIN.

Model SB-5500 Automatic Balancer System Controller



Quick Detachable
Display

Multi-Channel Status
Indicators

Large, High Resolution
Colour Display

Intuitive Menu
Interface

Benefits

- Increases throughput by saving setup time
- Improves part quality by automatically balancing to 0.02 micron
- All-digital electronic design increases operating life and reliability
- Easy to install and operate
- Longer life for grinding wheels, dressing wheels and spindle bearing
- Works with existing SBS installations
- Profibus, Ethernet and USB 2.0 communication compatibility
- International adaptability: voltage, frequency, communication, and display language
- Four-channel capability reduces costs by permitting balancing of multiple machines
- Backed by world-class SBS customer service

SBS strengthens its reputation as the world leader in automatic dynamic balancing and process monitoring for the grinding industry with the SB-5500 controller. With its all-digital electronic design, compact size and larger high resolution detachable display, the SB-5500 provides unsurpassed accuracy (up to 0.02 micron), speed (300-30,000rpm) and flexibility (four-channel capability).

The SB-5500 is easy to install and easy to use. Quick setups and dynamic graphic displays keep you well informed and in control of the grinding process. Optional virtual screen software lets you see readings on your existing monitor, or detach the display panel for installation where you want it. As an inexpensive and permanent installation, the SB-5500 takes the challenge out of grinding wheel balancing, helping you to improve part quality, increase efficiency, and save money.

Productivity through Precision.



SPECIFICATIONS Model SB-5500 Controller

Physical Features

Multiple Device Control

Four (4) available slots accept these control cards:

- SB-5512 Mechanical balancers with cable connection
- SB-5518 Hydro Balancers
- SB-5522 Acoustic Emissions Monitoring System (AEMS)
- SB-5532 Mechanical balancers with non-contact connection
- SB-5543 Manual balance control

SB-4500 Compatible

Operates with existing balancers/cables, sensors, CNC/PCL hardwire interface

Display

Type: Colour TFT LCD
Active area: 480H x 272V pixel
2.74 inch [95mm] x 2.12 inch [53.86mm]

Multi-language Capability

English, Chinese, French, German, Italian, Polish, Russian, Spanish, Swedish

Communication Interfaces

Ethernet TCP/IP, USB 2.0, Profibus DP, CNC/PLC hardwire Interface (opto-isolated outputs)

DC or AC Power Options

DC Supply: Input 21 VDC to 28 VDC. 5.5A max at 21 VDC. Reverse voltage protected.

AC Supply: 100-120 VAC, 50/60 Hz, 2A max; 200-240 VAC, 50/60 Hz, 1A max. Main supply voltage fluctuations not to exceed +/- 10% of nominal supply voltage.



The Model SB-5500 Controller with SBS Balancing System sensor connectors, adapters and balancing head.

Performance

RPM Reporting

300 to 30,000 RPM

Wide Vibration Range

50 µg to 1.25g

Vibration Display Resolution

Three user selectable options

1)	0.1 µm	0.01 mil	0.01 mm/s	1 mil/s
2)	0.01 µm	0.001 mil	0.001 mm/s	0.1 mil/s
3)	0.001 µm	0.001 mil	0.001 mm/s	0.01 mil/s

Vibration Display Repeatability

6,000 RPM ±1% @ 5.0 µm
300 – 30,000 RPM ±2% @ 50:1 signal to noise

Vibration Display Accuracy

6,000 RPM ±2% @ 5.0 µm
300 – 30,000 RPM ±4% @ 50:1 signal to noise

Auto-Balance Resolution

0.02 microns displacement at 6,000 RPM

Vibration Filter

Custom digital filter has bandwidth +/- 3% of measurement RPM

Safety and Environmental

Certifications

ETL and CE certified

Environmental and Installation Conditions

Pollution degree 2
Installation category II
IP54, NEMA 12
Environmental temperature range: 5°C to +55°C

For more information on Schmitt Balancing Systems, contact your nearest SBS Distributor Sales Representative or call Schmitt Industries.



A Product Line of Schmitt Industries, Inc.



Schmitt Europe Ltd

Ground Floor Unit 2
Leofric Court, Progress Way
Binley Industrial Estate
Coventry, CV3 2NT, England
enquiries@schmitt.co.uk
Tel: +44-(0)2476-651774
Fax: +44-(0)2476-450456
www.schmitteurope.com

Schmitt Industries, Inc.

2765 NW Nicolai Street
Portland, Oregon 97210-1818 USA
sbs-sales@schmitt-ind.com
Tel.: +1 503 227 7908
Fax: +1 503 223 1258
www.schmitt-ind.com